



## Portable Petrol Engine Driven Single-Phase Generator Output Power 3 kVA single-phase

### Standard Features

Low oil level cut out device  
 2 x 230 V - 50 Hz Single-phase Schuko outlets protected by circuit breaker  
 1 x 12V DC battery charger outlet protected by fuse

### Factory Options

Not available

### Accessories On Request

Not available

#### AC GENERATOR - 50 Hz

Type	synchronous
Single-Phase Power (stand by)	3 kVA - 230 V
Battery Charger	120 W - 12 V - 10 A - CC
Power Factor	0,8
Insulation Class	H
Mechanical Protection	IP 23

#### NOISE LEVEL

LWA 95	(70 dB at 7m)
Homologated in accordance with the "Directive 2000/14/CE"	

#### PETROL ENGINE - 3000 RPM

Type	<b>Honda GX 160 OHV</b> - 1 cyl. - 5,5 HP (4 kWm) - 163 cm <sup>3</sup>
Fuel	petrol
Cooling system	<b>air</b>
Starting system	manual recoil
Fuel tank capacity	3,6 l
Fuel consumption @ 75%	1,3 l/h

#### DIMENSIONS AND WEIGHT

L x W x H	585 x 360 x 410 mm
Net Weight	42 kg

SPECIFICATIONS AND PICTURES INTRODUCED HERE ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE

Pronk Machinery B.V. - Veilingweg 70 - 1749EJ Warmenhuizen - The Netherlands - info@pronk-machinery.nl - +316 226 753742