



**Portable Petrol Engine Driven Single-Phase Generator  
Output Power 5 kVA single-phase**

**Standard Features**

- Low oil level cut out device
- 2 x 230 V - 50 Hz Single-phase Schuko outlets protected by circuit breaker
- 1 x 12V DC battery charger outlet protected by fuse

**Factory Options**

Not available

**Accessori a Richiesta**

Not available

**AC GENERATOR - 50 Hz**

Type	synchronous
Single-Phase Power (stand by)	5 kVA - 230 V
Battery Charger	120 W - 12 V - 10 A - CC
Power Factor	0,8
Insulation Class	H
Mechanical Protection	IP 23

**NOISE LEVEL**

LWA 95 (70 dB at 7m)

**PETROL ENGINE - 3000 RPM**

Type	<b>Honda GX 270 OHV</b> - 1 cil. - 9 CV (6,6 kWm) - 270 cm <sup>3</sup>
Fuel	petrol
Cooling system	<b>air</b>
Starting system	manual recoil
Fuel tank capacity	6 l
Fuel consumption @ 75%	2,2 l/h

**DIMENSIONS AND WEIGHT**

L x W x H 720 x 480 x 515 mm  
Net Weight 63 kg

SPECIFICATIONS AND PICTURES INTRODUCED HERE ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE

Ú{ } \ Á ¢ £ ¤ ¥ ¦ § ¨ © ª « ¬ ® ¯ ° ± ² ³ ´ µ ¶ · ¸ ¹ º » ¼ ½ ¾ ¿ À Á Â Ã Ä Å Æ Ç È É Ê Ë Ì Í Î Ï Ñ Ò Ó Ô Õ Ö × Ø Ù Ú Û Ü Ý Þ à á â ã ä å æ ç è é ê ë ì í î ï ð ñ ò ó ô õ ö ÷ ø ù ú û ü ý þ ÿ