

**PORTABLE THREE-PHASE POWER GENERATOR / OUTPUT POWER
7,5 KVA THREE-PHASE AND 4 KVA SINGLE-PHASE /
PETROL ENGINE 3000 RPM**

Gen Set Features	<ul style="list-style-type: none">+ Low oil level cut out device+ 1 x 16A, 400 V - 50 Hz three-phase EEC socket protected by circuit breaker+ 1 x 16A, 230 V - 50 Hz single-phase EEC socket protected by circuit breaker+ Earth Leakage Circuit Breaker (ELCB)
Gen Set Options (available as factory options)	<ul style="list-style-type: none">+ Not available
Accessories on Request	<ul style="list-style-type: none">+ Trolley: two-wheels and handles
Noise Level	+ LWA 97 (72 dB at 7m)
AC Generator 50 Hz	<ul style="list-style-type: none">+ Type synchronous+ Three-phase power (max.) 7,5 kVA - 400 V+ Single-phase power (max.) 4 kVA - 230 V+ Power Factor 0,8
Petrol Engine 3000 rpm	<ul style="list-style-type: none">+ Type Honda GX 390 OHV - 1 cyl. - 13 HP (9,6 kWm) - 390 cm³+ Fuel petrol+ Cooling system air+ Starting system manual recoil+ Fuel tank capacity 6,5 l+ Fuel consumption @ 75% 2,9 l/h
Other Features	<ul style="list-style-type: none">+ Insulation Class H+ Mechanical Protection IP 23+ Dimensions (L x W x H) 730 x 480 x 520 mm+ Dry Weight 80 kg

EA 7/3 GH