

**SINGLE-PHASE POWER GENERATOR / OUTPUT POWER 11 KVA**  
**SINGLE-PHASE / PETROL ENGINE 3000 RPM**

<b>Gen Set Features</b>	<ul style="list-style-type: none"> <li>+ Low oil level cut out device</li> <li>+ 12 V built-in battery with electric start</li> <li>+ 1 x 32 A, 230 V - 50 Hz single-phase EEC socket protected by circuit breaker</li> <li>+ 1 x 16 A, 230 V - 50 Hz single-phase EEC socket protected by circuit breaker</li> <li>+ Earth Leakage Circuit Breaker (ELCB)</li> <li>+ Voltmeter</li> <li>+ Hourmeter</li> <li>+ Central lifting eye</li> </ul>	
<b>Gen Set Options</b> (available as factory options)	<ul style="list-style-type: none"> <li>+ Version with different voltages</li> <li>+ 60 Hz version</li> <li>+ AMF/ATS panel for auto start operation</li> </ul>	
<b>Accessories on Request</b>	+ Trolley	two-wheels and handles
<b>Noise Level</b>	+ Lwa 98	(73 dB a 7 m)
<b>AC Generator 50 Hz</b>	<ul style="list-style-type: none"> <li>+ Type synchronous</li> <li>+ Single-phase p. (stand-by) 11 kVA - 230 V</li> <li>+ Single-phase p. (prime) 10 kVA - 230 V</li> <li>+ Power Factor 0,8</li> </ul>	
<b>Petrol Engine 3000 rpm</b>	<ul style="list-style-type: none"> <li>+ Type <b>Honda GX 630 OHV</b> - 2 cil. 14,1 CV (10,5 kWm) - 688 cm3</li> <li>+ Fuel Petrol</li> <li>+ Cooling system air</li> <li>+ Starting system electric</li> <li>+ Fuel tank capacity 29 l</li> <li>+ Fuel consumption @ 75% 6 l/h (@ 3600 rpm)</li> </ul>	
<b>Other features</b>	<ul style="list-style-type: none"> <li>+ Insulation Class H</li> <li>+ Ambient temperature 40 °C</li> <li>+ Altitude 1000 mt</li> <li>+ Mechanical Protection IP 23</li> <li>+ Dimensions (L x W x H) 940 x 488 x 823 mm</li> <li>+ Dry weight 148 kg</li> </ul>	

**FX 12 GH**

