

SILENT 6000 B/A








	OUTPUT POWER 3,6 KW SINGLE-PHASE PETROL ENGINE 3000 RPM
Standard Features	+ Low oil level cut out device + 12 V built-in battery + 1 x 230V - 16A EEC single-phase socket + Power output protection + Earth Leakage Circuit Breaker + Voltmeter + Hourmeter + Fixed wheels and concealable handles for moving
Options available as factory options	+ Versions with different voltages + 60Hz version + Foreseen for AMF-ATS or Remote control operation
Accessories on request	+ AMF/ATS panel for auto start operation + Remote control
Noise level	+ Lwa 89 (64 dB at 7 m)
AC generator 50Hz	+ Type: synchronous + Single-phase power (stand-by): 3,6 kW - 230V + Single-phase power (prime): 3,2 kW - 230V + Power factor: cos φ 1
Petrol Engine 3000 rpm	+ Type: Honda GX270 - 1 cyl 270 cm ³ + Max power: 8,2 hp (6 kWm) + Starting system: electric (12Vdc) + Cooling system: air + Fuel consumption @ 75%: 2,2 l/h
Other features	+ Insulation Class: H + Ambient temperature: 40 °C (*) + Altitude: 1000 m (*) + Mechanical Protection: IP 23 + Fuel tank capacity: 10,5 1 + Dimensions (L x W x H): 941 x 614 x 720 mm + Dry weight: 125 kg

SUPER SILENCED POWER GENERATOR



Veilingweg 70 - 1749 EJ Warmenhuizen - The Netherlands - Tel.: (+31)226-753742 - Email: info@pronk-machinery.nl

(*) - For altitude and temperature values higher than those listed above, please consult the manufacturer to verify the available power.