

mase GENERATORS



SILENT 8000 B/A



mase



Your partner in power solutions - Worldwide delivery

SUPER SILENCED POWER GENERATOR
OUTPUT POWER 5 KW SINGLE-PHASE
PETROL ENGINE 3000 RPM

Standard Features	<ul style="list-style-type: none"> + Low oil level cut out device + 12 V built-in battery + 1 x 230V - 32A EEC single-phase socket + 1 x 230V - 16A EEC single-phase socket + Power output protection + Earth Leakage Circuit Breaker + Voltmeter + Hourmeter + Fixed wheels and concealable handles for moving
Options available as factory options	<ul style="list-style-type: none"> + Versions with different voltages + 60Hz version + Foreseen for AMF-ATS or Remote control operation
Accessories on request	<ul style="list-style-type: none"> + AMF/ATS panel for auto start operation + Remote control
Noise level	+ Lwa 89 (64 dB at 7 m)
AC generator 50Hz	<ul style="list-style-type: none"> + Type: synchronous + Single-phase power (stand-by): 5 kW- 230V + Single-phase power (prime): 4,5 kW- 230V + Power factor: $\cos \phi$ 1
Petrol Engine 3000 rpm	<ul style="list-style-type: none"> + Type: Honda GX390 - 1 cyl. - 390 cm³ + Max power: 11,5 hp (8,7 kWm) + Starting system: manual + Cooling system: air + Fuel consumption @ 75%: 3,3 l/h
Other features	<ul style="list-style-type: none"> + Insulation Class: H + Ambient temperature: 40 °C (*) + Altitude: 1000 m (*) + Mechanical Protection: IP 23 + Fuel tank capacity: 10,5 l + Dimensions (L x W x H): 941 x 614 x 720 mm + Dry weight: 138 kg



Your partner in power solutions - Worldwide delivery

Veilingweg 70 - 1749 EJ Warmenhuizen - The Netherlands - Tel.: (+31)226-753742 - Email: info@pronk-machinery.nl

(*) - For altitude and temperature values higher than those listed above, please consult the manufacturer to verify the available power.

In line with our continued development, innovation and voice of customer program, we reserve the right to change data without notice.