

# LT 10000 K





Your partner in power solutions - Worldwide delivery





## SUPER SILENCED SINGLE-PHASE POWER GENERATOR / OUTPUT POWER 8 kW SINGLE-PHASE / DIESEL ENGINE 1500 RPM

#### **Gen Set Features**

- + Control panel with voltmeter and hour meter; with auto engine protection shutdown system in case of:
- + low oil pressure
- + high engine temperature

- + 12V built-in battery with electric start
- + fuellevel gauge
- + emergency stop push-button
- + 1x16 A 230V single-phase socket protected by circuit breaker
- + 3 stabilizers
- + 7 mt lighting tower with 4x1500W halogen lamps
- + 2 wheels site tow undercarriage

#### Options

(available as factory options)

- + floodlight with metal halide lamps
- + floodlight with LED lamps
- + hydraulic lifting

- + 2 wheels road tow
- + low temperature kit
- + dusk sesor
- + homologation to directive 2000/14/EC

#### Accessories on Request

+ not available

### **Noise Level**

+ Lwa 96

(71 dB a 7 m)

## AC Generator 50 Hz

- + type: synchronous
- + single-phase power (stand by): 8 kW 230 V
- + single-phase power (prime): 7.2 kW 230 V
- + power Factor: cosΦ0.8

#### Diesel Engine 1500 rpm

- + type: KUBOTA D1105-E -3 cyl. 12.7 HP 1123 cm<sup>3</sup>
- + fuel: diesel
- + cooling system: water
- + starting system: electric
- + fuel tank capacity: 100 L
- + fuel consumption @ 75%: 2 L/h

#### **Other Features**

- + insulation Class: H
- + ambient temperature: 40 °C (\*)
- + altitude: 1000 mt (\*)
- + mechanical Protection: IP 23
- + dimensions (L x W x H): 2935 x 1522 x 2395 mm
- + dimensions of the machine in operation (L x W x H): 2935 x 2612 x 8000 mm
- + dry weight: 655 kg



Your partner in power solutions - Worldwide delivery

Veilingweg 70 - 1749 EJ Warmenhuizen - The Netherlands - Tel.: (+31)226-753742 - Email: info@pronk-machinery.nl

(\*) - For altitude and temperature values higher than those listed above, please consult the manufacturer to verify the available power.