

LT 10000 P





Your partner in power solutions - Worldwide delivery





SUPER SILENCED SINGLE-PHASE POWER GENERATOR / OUTPUT POWER 7,2 kW SINGLE-PHASE / DIESEL ENGINE 1500 RPM

Gen Set Features

- + Control panel with voltmeter and hour meter; with auto engine protection shutdown system in case of:
- + low oil pressure
- + high engine temperature

- + 12V built-in battery with electric start
- + fuel level gauge
- + emergency stop push-button
- + 1x16A230V single-phase socket protected by circuit breaker
- + 3 stabilizers
- + 7 mt lighting tower with 4x1500W halogen lamps
- + 2 wheels site tow undercarriage

Options

(available as factory options)

- + floodlight with metal halide lamps
- + floodlight with LED lamps
- + hydraulic lifting

- + 2 wheels road tow
- + low temperature kit
- + dusk sesor
- + homologation to directive 2000/14/EC

Accessories on Request

+ not available

Noise Level

+ Lwa 96

(71 dB a 7 m)

AC Generator 50 Hz

- + type: synchronous
- + single-phase power (stand by): 7.2 kW 230 V
- + single-phase power (prime): 6.4 kW 230 V
- + power Factor: cos Ф 0.8

Diesel Engine 1500 rpm

- + type: PERKINS 403D-11G 3 cyl. 12,4 HP 1028 cm³
- + fuel: diesel
- + cooling system: water
- + starting system: electric
- + fuel tank capacity: 100 L
- + fuel consumption @ 75%: 2 L/h

Other Features

- + insulation Class: H
- + ambient temperature: 40 °C (*)
- + altitude: 1000 mt (*)
- + mechanical Protection: IP 23
- + dimensions (L x W x H): 2935 x 1522 x 2395 mm
- + dimensions of the machine in operation (L x W x H): 2935 x 2612 x 8000 mm
- + dry weight: 655 kg



Your partner in power solutions - Worldwide delivery

Veilingweg 70 - 1749 EJ Warmenhuizen - The Netherlands - Tel.: (+31)226-753742 - Email: info@pronk-machinery.nl

(*) - For altitude and temperature values higher than those listed above, please consult the manufacturer to verify the available power.