



**SILENCED POWER GENERATOR
OUTPUT POWER 11 KVA THREE-PHASE AND 3,6 KVA SINGLE-PHASE
DIESEL ENGINE 1500 RPM**

<p>Standard Features</p>	<ul style="list-style-type: none"> + Auto engine protection shutdown system with warning lights in case of: <ul style="list-style-type: none"> - battery charger failure - low fuel level - low oil pressure - high water temperature + 1 x 32A, 400V three-phase EEC socket + 1 x 32A, 230V single-phase EEC socket + 12V built-in battery + Hourmeter + Voltmeter + Emergency stop button + Fuel level visual indicator + Foreseen for AMF-ATS or Remote control operation + Earth leakage circuit breaker + Power output protection + Engine oil drain pipe + Central lifting eye
<p>Options available as factory options</p>	<ul style="list-style-type: none"> + Versions with different voltages + 60Hz version + Spark arrester muffler + Automatic voltage regulator
<p>Accessories on request</p>	<ul style="list-style-type: none"> + Quadro per avviamento automatico (AMF/ATS) + Remote Start/Stop kit by cable (20 m)
<p>Noise level</p>	<ul style="list-style-type: none"> + Lwa 90 (65 dB at 7 m)
<p>AC generator - 50Hz</p>	<ul style="list-style-type: none"> + Type: synchronous + Three-phase power (stand-by): 11kVA - 400V + Three-phase power (prime): 10kVA - 400V + Single-phase power (max.): 3,6kVA - 230V + Power factor: $\cos \varphi$ 0,8
<p>Diesel Engine 1500 rpm</p>	<ul style="list-style-type: none"> + Type: Perkins 403A-11G - 3 cyl. - 1131 cm³ + Max power: 12,4 hp (9,2 kWm) + Starting system: electric (12Vdc) + Cooling system: water + Fuel consumption @ 75%: 2,3 l/h
<p>Other features</p>	<ul style="list-style-type: none"> + Insulation Class: H + Ambient temperature: 40 °C (*) + Altitude: 1000 m (*) + Mechanical Protection: IP 23 + Fuel tank capacity: 40 l + Dimensions (L x W x H): 1650 x 700 x 980 mm + Dry weight: 390 kg

(*) - For altitude and temperature values higher than those listed above, please consult the manufacturer to verify the available power.